


INSTALLATION AND SERVICE MANUAL


For installation of Jet cylindrical and square wall down light

Product drawing (dimensions)


SUITABLE FOR WET LOCATIONS




UJE-30391



UJE-30411




MOUNTING DETAIL




NOTE


Mounts over a 3" Octagonal Junction box.



①




②




③

Using the nylon washers and the 7mm. nut driver secure the back plate to the wall

④




Ensure watertight seal using UL approved silicone based sealant.



⑤

Connect Power and Ground Wire.



⑥

Ligman RGBW/DMX & 0-10v dimming fixtures are provided with 5 wire, underwater rated 600v SO power cord. This consists of hot, neutral and ground, as well as twisted, shielded DMX +, DMX - and ground wire.

Notice to installer :

- 1.WIRING INSTRUCTIONS Warning :** RISK OF FIRE AND ELECTRICAL SHOCK. : FIXTURE MUST BE INSTALLED BY A QUALIFIED ELECTRICIAN ONLY>FIXTURE IS INTENDED FOR INSTALLATION IN ACCORDANCE WITH THE NATIONAL ELECTRICAL CODE, LOCAL AND FEDERAL CODE SPECIFICATIONS. DISCONNECT POWER BEFORE SERVICING.
- 2.This fixture has a VOLTAGE SPECIFIC BALLAST,**Check that the supply voltage is the same as the installed ballast voltage.

Ligman Lighting USA

7144 NW Progress Court, Hillsboro
Oregon, 97124, USA
Tel : 503 645 0500 | Fax : 503 645 8100


www.ligmanlightingusa.com

DMX WIRING DIAGRAM

LIGMAN
COLOR

GREEN	GROUND
BLACK	120/277 HOT
WHITE	NEUTRAL
YELLOW	DMX GROUND
PURPLE	DMX +
GREY	DMX -

SINGLE FIXTURE CONNECTION



FOR LOOPING TO MULTIPLE FIXTURES

