


LUMINAIRE SPECIFICATION


IP65 : Suitable for Wet Locations IK08 : Impact Resistant (Vandal Resistant)









Bottom view





Mounting detail



Ordering Example : UGA - 31982 - T6-150w - 120v - Options

PROJECT:

UGA-31982

Gandalf 21 wall area light luminaire Type II

A small size wall mount area light for metal halide or high pressure sodium lamps 70-150w and LED. A high quality asymmetrical reflector design creates broad light distribution. The high ingress protection allows these luminaires to be wall mounted for upward or downward lighting. The Gandalf can be aimed to suit specific light patterns with the adjustable arm. Designed for lighting footpaths, car parks, building facades, under canopies, roads and signs.

Low copper content corrosion resistant die-cast aluminum body. Integral control gear. All external hardware in stainless steel. Durable silicone rubber gasket and hinged clear toughened glass with quick release aluminum clips for in-position lamp replacement. Anodized high purity 95% reflective aluminum reflector. The luminaire is treated with a chemical chromatized protection before powder coating, ensuring high corrosion resistance.

Physical Data Length: 22.48" Height: 4.72" Weight: 20.2 lbs

Lamp

🗆 T6 CMH 150w 🕬 🛥 (For More Lamp options including LED, please Consult the Catalogue, Website or Contact The Ligman Lighting Factory)

Voltage (Please Specify)

□ 120V □ 277V

□ Other

Options (Please Specify) □ F - Frosted Lens

C - Clear Lens

Color (Please Specify)

D 01-Black - RAL 9011 D 03-White - RAL 9003 D 05-Matt Silver - RAL 9006 □ 06-Bronze - RAL 6014

- D 02- Dark Grey RAL 7043
- □ 04 Metallic Śilver RAL 9006
- □ 07- Custom RAL





DATE:



QUANTITY: Ligman Lighting USA reserves the right to change specifications without prior notice, please contact factory for latest information. Due to the continual improvements in LED technology data and components may change without notice.

NOTE: