

INSTALLATION AND SERVICE MANUAL

For installation of Columbus sheppards crook medium shade post top COB.
Model. UCO-20169.

Product drawing (dimensions)
SUITABLE FOR WET LOCATIONS

TOOL

2.5, 4, 5

36.33"

26.32"

27.92"

36.29"

26.28"

27.84"

36.29"

26.28"

27.24"

36.29"

26.28"

27.84"

36.29"

26.28"

27.24"

SWEPT (1)
DOME (1)

SWEPT (1)
CONE (2)

STRAIGHT (2)
DOME (1)

STRAIGHT (2)
CONE (2)

Ø2.36"x3.5"

Ø2.99"x3.5"

TENON POST TOP

9.84"

7.08"

Ø0.86"

9.84"

6.57"

0.86"x1.96"

STEEL POST
MOUNTING DETAIL

ALUMINIUM POST
MOUNTING DETAIL

8.2'

①

Connect Power and Ground Wire.

②

③

Connect Power and Ground Wire.

Notice to installer :

- 1.WIRING INSTRUCTIONS Warning : RISK OF FIRE AND ELECTRICAL SHOCK. : FIXTURE MUST BE INSTALLED BY A QUALIFIED ELECTRICIAN ONLY>FIXTURE IS INTENDED FOR INSTALLATION IN ACCORDANCE WITH THE NATIONAL ELECTRICAL CODE, LOCAL AND FEDERAL CODE SPECIFICATIONS. DISCONNECT POWER BEFORE SERVICING.**
- 2.This fixture has a VOLTAGE SPECIFIC BALLAST,Check that the supply voltage is the same as the installed ballast voltage.**

Ligman Lighting USA

7144 NW Progress Court, Hillsboro
Oregon, 97124, USA
Tel : 503 645 0500 | Fax : 503 645 8100

www.ligmanlightingusa.com

UCO-20169 11/09/17 REV.1 1/2



FM-TS-13/25-05-2007-REV.2

