



For installation of Duomo wall light LED.
Model. UDU-30787.

Product drawing (dimensions)

SUITABLE FOR WET LOCATIONS




MOUNTING DETAIL




NOTE

Mounts over a 3" Octagonal Junction box.



1



2

Center the Back Plate over the J Box and Secure the back plate to the wall


3

Ensure watertight seal using UL approved silicone based sealant.




4


Connect Power and Ground Wire.




5




6




7



8



9



Notice to installer :

- 1. WIRING INSTRUCTIONS Warning : RISK OF FIRE AND ELECTRICAL SHOCK. : FIXTURE MUST BE INSTALLED BY A QUALIFIED ELECTRICIAN ONLY > FIXTURE IS INTENDED FOR INSTALLATION IN ACCORDANCE WITH THE NATIONAL ELECTRICAL CODE, LOCAL AND FEDERAL CODE SPECIFICATIONS. DISCONNECT POWER BEFORE SERVICING.**
- 2. This fixture has a VOLTAGE SPECIFIC BALLAST, Check that the supply voltage is the same as the installed ballast voltage.**

Ligman Lighting USA

7144 NW Progress Court, Hillsboro
Oregon, 97124, USA
Tel : 503 645 0500 | Fax : 503 645 8100

www.ligmanlightingusa.com

UDU-30787 03/09/14 REV.0

1/1



FM-TS-13/25-05-2007-REV.2