








For installation of Duomo sheppards crook medium shade wall light.
Model. UDU-30201-30210.

Product drawing (dimensions)




SUITABLE FOR WET LOCATIONS


NOTE

Mounts over a 3" Octagonal Junction box.

1




2




Install Gasket between wall and Back Plate.

3



Position the Back Plate over the J Box and Secure the back plate to the wall

4



Connect Power and Ground Wire.

Notice to installer :

- 1.WIRING INSTRUCTIONS Warning : RISK OF FIRE AND ELECTRICAL SHOCK. : FIXTURE MUST BE INSTALLED BY A QUALIFIED ELECTRICIAN ONLY>FIXTURE IS INTENDED FOR INSTALLATION IN ACCORDANCE WITH THE NATIONAL ELECTRICAL CODE, LOCAL AND FEDERAL CODE SPECIFICATIONS. DISCONNECT POWER BEFORE SERVICING.**
- 2.This fixture has a VOLTAGE SPECIFIC BALLAST,Check that the supply voltage is the same as the installed ballast voltage.**

Ligman Lighting USA

7144 NW Progress Court, Hillsboro
Oregon, 97124, USA
Tel : 503 645 0500 | Fax : 503 645 8100

www.ligmanlightingusa.com

UDU-30201/07/06/14/REV.0

1/2



FM-TS-13/25-05-2007-REV.2

