


For installation of Jet cylindrical Wall up-down light.
Model. UJE-30421, UJE-30431-30432, UJE-30441.


Product drawing (dimensions)

SUITABLE FOR WET LOCATIONS




NOTE

Mounts over
a 3" Octagonal
Junction box.




①

②




③

Using the nylon washers
and the 7mm. nut driver
secure the back
plate to the wall




Ensure watertight seal using UL
approved silicone based sealant.

④




Connect Power
and Ground Wire.


⑤




⑥



⑦



⑧



Notice to installer :

- 1.WIRING INSTRUCTIONS** Warning : RISK OF FIRE AND ELECTRICAL SHOCK. : FIXTURE MUST BE INSTALLED BY A QUALIFIED ELECTRICIAN ONLY>FIXTURE IS INTENDED FOR INSTALLATION IN ACCORDANCE WITH THE NATIONAL ELECTRICAL CODE, LOCAL AND FEDERAL CODE SPECIFICATIONS. DISCONNECT POWER BEFORE SERVICING.
- 2.This fixture has a VOLTAGE SPECIFIC BALLAST,Check that the supply voltage is the same as the installed ballast voltage.**

Ligman Lighting USA

7144 NW Progress Court, Hillsboro
Oregon, 97124, USA
Tel : 503 645 0500 | Fax : 503 645 8100

www.ligmanlightingusa.com

UJE-30421/23/06/14/REV.2

1/1



FM-TS-13/25-05-2007-REV.2