



For installation of Jet 11,15 cylindrical and square wall up-down light.  
Model. UJE-30435-30436 and UJE-30685-30686.

## Product drawing (dimensions)




UJE-30435-UJE-30436




UJE-30685-UJE-30686

## SUITABLE FOR WET LOCATIONS




MOUNTING DETAIL




TOOL

1




**NOTE**  
Mounts over a 3"  
Octagonal Junction box.

2




3

Using the nylon washers  
and the 7mm. nut driver  
secure the back  
plate to the wall




Ensure watertight seal using UL  
approved silicone based sealant.

4



Connect Power  
and Ground Wire.

5



## Notice to installer :

1. **WIRING INSTRUCTIONS** Warning : RISK OF FIRE AND ELECTRICAL SHOCK. : FIXTURE MUST BE INSTALLED BY A QUALIFIED ELECTRICIAN ONLY>FIXTURE IS INTENDED FOR INSTALLATION IN ACCORDANCE WITH THE NATIONAL ELECTRICAL CODE, LOCAL AND FEDERAL CODE SPECIFICATIONS. DISCONNECT POWER BEFORE SERVICING.
2. This fixture has a **VOLTAGE SPECIFIC BALLAST**, Check that the supply voltage is the same as the installed ballast voltage.

Ligman Lighting USA

7144 NW Progress Court, Hillsboro  
Oregon, 97124, USA  
Tel : 503 645 0500 | Fax : 503 645 8100

www.ligmanlightingusa.com

UJE-30435/26/06/14/REV.2

1/2



FM-TS-13/25-05-2007-REV.2

