





For installation of Syndy symmetrical indirect light wall light.
Model. U30911 - U30913.

Product drawing (dimensions)




USY-30911-USY-30913




USY-30914-USY-30916


SUITABLE FOR WET LOCATIONS



SPIGOT WALL LIGHT



MOUNTING DETAIL




NOTE

Mounts over a 3\"/>





1




2

Ensure watertight seal using UL approved silicone based sealant.

3




4



5

Connect Power and Ground Wire.

6



Notice to installer :

- 1.WIRING INSTRUCTIONS Warning : RISK OF FIRE AND ELECTRICAL SHOCK. : FIXTURE MUST BE INSTALLED BY A QUALIFIED ELECTRICIAN ONLY>FIXTURE IS INTENDED FOR INSTALLATION IN ACCORDANCE WITH THE NATIONAL ELECTRICAL CODE, LOCAL AND FEDERAL CODE SPECIFICATIONS. DISCONNECT POWER BEFORE SERVICING.**
- 2.This fixture has a VOLTAGE SPECIFIC BALLAST,Check that the supply voltage is the same as the installed ballast voltage.**

Ligman Lighting USA

7144 NW Progress Court, Hillsboro
Oregon, 97124, USA
Tel : 503 645 0500 | Fax : 503 645 8100

www.ligmanlightingusa.com

USY-30911/07/07/14/REV.0
1/2



FM-TS-13/25-05-2007-REV.2

