



For installation of Tango cylindrical and square surface exterior down light


Product drawing (dimensions) SUITABLE FOR WET LOCATIONS




U80311 - U80315 MOUNTING DETAIL










U80321 - U80325 MOUNTING DETAIL



1



NOTE Mounts over a 3" or 4" Octagonal Junction box.



Notice to installer :

- 1.WIRING INSTRUCTIONS** Warning : RISK OF FIRE AND ELECTRICAL SHOCK. : FIXTURE MUST BE INSTALLED BY A QUALIFIED ELECTRICIAN ONLY>FIXTURE IS INTENDED FOR INSTALLATION IN ACCORDANCE WITH THE NATIONAL ELECTRICAL CODE, LOCAL AND FEDERAL CODE SPECIFICATIONS. DISCONNECT POWER BEFORE SERVICING.
- 2.This fixture has a VOLTAGE SPECIFIC BALLAST,Check that the supply voltage is the same as the installed ballast voltage.**

Ligman Lighting USA

Tanasbourne Commerce Center
3302 Nw 211th Terrace
Hillsboro Oregon 97124
Tel : 503-645-0500, Fax : 503-645-8100

www.ligmanlightingusa.com

U 80311/14/07/12/REV.0

1/1



FM-TS-13/25-05-2007-REV.2