


INSTALLATION AND SERVICE MANUAL



For Installation of Gini wall surface luminaire LED
Model. UGN-30041,UGN-30051,UGN-30061,UGN-30071,UGN-30081 and UGN-30091


Product drawing (dimensions) SUITABLE FOR WET LOCATIONS

One side





Top view Bottom view

Two side




Top view Bottom view



Model No.	Dimension				
	L1	D1	D2	D3	D4
UGN-30041	23.46"	23.30"	23.30"	7.08"	7.08"
UGN-30061	35.19"	34.84"	30.90"	9.84"	11.22"
UGN-30081	46.92"	46.45"	44.88"	9.05"	8.66"


Model No.	Dimension				
	L1	D1	D2	D3	D4
UGN-30051	23.46"	23.30"	23.30"	7.08"	7.08"
UGN-30071	35.19"	34.84"	30.90"	9.84"	11.22"
UGN-30091	46.92"	46.45"	44.88"	9.05"	8.66"




MOUNTING DETAIL

NOTE- Mounts over Single gang horizontally mounted junction box


①




②




③




④



⑤



⑥



Connect Power and Ground Wire

Notice to installer :

- 1.WIRING INSTRUCTIONS** Warning : RISK OF FIRE AND ELECTRICAL SHOCK. : FIXTURE MUST BE INSTALLED BY A QUALIFIED ELECTRICIAN ONLY>FIXTURE IS INTENDED FOR INSTALLATION IN ACCORDANCE WITH THE NATIONAL ELECTRICAL CODE, LOCAL AND FEDERAL CODE SPECIFICATIONS. DISCONNECT POWER BEFORE SERVICING.
- 2.This fixture has a VOLTAGE SPECIFIC BALLAST**,Check that the supply voltage is the same as the installed ballast voltage.

Ligman Lighting USA

7144 NW Progress Court, Hillsboro
Oregon, 97124, USA
Tel : 503 645 0500 | Fax : 503 645 8100

www.ligmanlightingusa.com

ISO 9001
ISO 14001
BUREAU VERITAS
Certification



FM-TS-13/25-05-2007-REV.2

