








INSTALLATION AND SERVICE MANUAL

For installation of Gandalf 26 Floodlight LED.



Ligman RGBW/DMX & 0-10v dimming fixtures are provided with 5 wire, underwater rated 600v SO power cord. This consists of hot, neutral and ground, as well as twisted, shielded DMX +, DMX - and ground wire.







Notice to installer :

- 1.WIRING INSTRUCTIONS Warning :** RISK OF FIRE AND ELECTRICAL SHOCK. : FIXTURE MUST BE INSTALLED BY A QUALIFIED ELECTRICIAN ONLY>FIXTURE IS INTENDED FOR INSTALLATION IN ACCORDANCE WITH THE NATIONAL ELECTRICAL CODE, LOCAL AND FEDERAL CODE SPECIFICATIONS. DISCONNECT POWER BEFORE SERVICING.
- 2.This fixture has a VOLTAGE SPECIFIC BALLAST,Check that the supply voltage is the same as the installed ballast voltage.**

Ligman Lighting USA

Tanasbourne Commerce Center
3302 Nw 211th Terrace
Hillsboro Oregon 97124
Tel : 503-645-0500, Fax : 503-645-8100


www.ligmanlightingusa.com



DMX WIRING DIAGRAM

GREEN	GROUND
BLACK	120/277 HOT
WHITE	NEUTRAL
YELLOW	DMX GROUND
PURPLE	DMX +
GREY	DMX -

SINGLE FIXTURE CONNECTION



FOR LOOPING TO MULTIPLE FIXTURES

