



LIGMAN
LIGHTING USA

Product drawing (dimensions)

Technical drawing of the 1000 Series Mounting Bracket, showing front, side, and mounting detail views with dimensions and tool requirements.

Front View Dimensions:

- Overall Height: 1'-6.99" OR 2'-7.01"
- Overall Width: 8.55"

Side View Dimensions:



- Top Section Width: 8.55"
- Top Section Height: 9.54"
- Bottom Section Height: 9.02"

Mounting Detail Dimensions:

- Outer Diameter: $\phi 3.25"$
- Inner Diameter: $\phi 0.62"$
- Mounting Flange Width: 8.17"
- Mounting Flange Thickness: 3.72"
- Bracket Thickness: 1.44"

Tools Required:

- 3/8" Hex Key
- Phillips Screwdriver
- Open End Wrench



1.WIRING INSTRUCTIONS Warning : RISK OF FIRE AND ELECTRICAL SHOCK. : FIXTURE MUST BE INSTALLED BY A QUALIFIED ELECTRICIAN ONLY>FIXTURE IS INTENDED FOR INSTALLATION IN ACCORDANCE WITH THE NATIONAL ELECTRICAL CODE, LOCAL AND FEDERAL CODE SPECIFICATIONS. DISCONNECT POWER BEFORE SERVICING.

2.This fixture has a VOLTAGE SPECIFIC BALLAST,Check that the supply voltage is the same as the installed ballast voltage.

Tanasbourne Commerce Center
3302 Nw 211th Terrace
Hillsboro Oregon 97124
Tel : 503-645-0500, Fax : 503-645-8100


UCO-10111/21/10/15/REV.2
1/2




FM-TS-13/25-05-2007-REV.2

⑥

NOTE
Connect power using
UL Approved waterproof
wire nuts.




⑦




Cable OD
Min 0.24"
Max 0.47"


⑧



⑨




⑩



⑪



⑫



⑬

