





INSTALLATION AND SERVICE MANUAL






For installation of Columbus sheppards crook medium shade wall light.
Model. UCO-30191-30200.

Product drawing (dimensions)



MOUNTING DETAIL




TOOL

SUITABLE FOR WET LOCATIONS


NOTE

Mounts over
a 3" Octagonal
Junction box.

1




2




Install Gasket between wall
and Back Plate.

3



Position the Back Plate
over the J Box and Secure
the back plate to the wall

4



Connect Power
and Ground Wire.

Notice to installer :

- 1.WIRING INSTRUCTIONS** Warning : RISK OF FIRE AND ELECTRICAL SHOCK. : FIXTURE MUST BE INSTALLED BY A QUALIFIED ELECTRICIAN ONLY>FIXTURE IS INTENDED FOR INSTALLATION IN ACCORDANCE WITH THE NATIONAL ELECTRICAL CODE, LOCAL AND FEDERAL CODE SPECIFICATIONS. DISCONNECT POWER BEFORE SERVICING.
- 2.This fixture has a VOLTAGE SPECIFIC BALLAST,**Check that the supply voltage is the same as the installed ballast voltage.

Ligman Lighting USA

7144 NW Progress Court, Hillsboro
Oregon, 97124, USA
Tel : 503 645 0500 | Fax : 503 645 8100

www.ligmanlightingusa.com

UCO-30191/07/06/14/REV.1

1/2



FM-TS-13/25-05-2007-REV.2

