



For Installation of Accessories Odessa 1 OD-50001, OD-50002 Floodlights, projectors.
Model. A80121 and A80214


Product drawing (dimensions)




HONEYCOMB LOUVRE
A80121




LINEAR SPREAD LENS
A80214



TOOL




1




2

HONEYCOMB LOUVRE



Torque: 2.0Nm.

LINEAR SPREAD LENS



Torque: 2.0Nm.

- LIGMAN standard products are supplied with the control gear 220-240V 50/60Hz.
The control gear for other voltages and frequencies is available upon request, please consult us for more details.
- LIGMAN luminaires are designed to conform IEC 60598 2-5 standard.
Technical amendments and modifications techniques reserved.

Ligman Lighting

Europe Headquarters
Ligman Europe s.r.o.
VGP Park Usti nad Labem, P2 120,
40317 Prestanov
Czech Republic
Tel. +420 477 071 500
sales.cz@ligman.com

www.ligman.com

M A80121/04/05/21/REV.2
1/2

Thailand Headquarters
Ligman Lighting Co., Ltd.
17/2 Moo 4, Monthong,
Bangnampreaw,
24150, Chachoengsao
Tel : +66 33 026 082
info@ligman.com

FM-TS-13-1/13-05-2563/REV.6

