










For installation of Eco Recessed location light LED.

Product drawing (dimensions)

SUITABLE FOR WET LOCATIONS



THIS BACKBOX IS PROVIDED WITH HOLES AND GASKETS TO SECURE TO BACKBOARD DURING INSTALLATION. IF THESE HOLES ARE NOT USED, THEY NEED TO BE PROPERLY SEALED TO PREVENT WATER SEEPING INTO THE FIXTURE. [A STAINLESS STEEL NUT AND BOLT PROPERLY TIGHTENED WITH SILICON CAULKING COULD BE USED]



Notice to installer :

- 1.WIRING INSTRUCTIONS** Warning : RISK OF FIRE AND ELECTRICAL SHOCK. : FIXTURE MUST BE INSTALLED BY A QUALIFIED ELECTRICIAN ONLY>FIXTURE IS INTENDED FOR INSTALLATION IN ACCORDANCE WITH THE NATIONAL ELECTRICAL CODE, LOCAL AND FEDERAL CODE SPECIFICATIONS. DISCONNECT POWER BEFORE SERVICING.
- 2.This fixture has a VOLTAGE SPECIFIC BALLAST,Check that the supply voltage is the same as the installed ballast voltage.**

Ligman Lighting USA

Tanasbourne Commerce Center
3302 Nw 211th Terrace
Hillsboro Oregon 97124
Tel : 503-645-0500, Fax : 503-645-8100

www.ligmanlightingusa.com

U 40571/19/01/12/REV.0

1/1



FM-TS-13/25-05-2007-REV.2