



For installation of Tango cylindrical and square wall down light LEDs.
Model. UTA-31285 and UTA-31295.

Product drawing (dimensions)


SUITABLE FOR WET LOCATIONS




UTA-31285



UTA-31295




MOUNTING DETAIL




TOOL


NOTE
Mounts over
a 3" Octagonal
Junction box.



1




2




3

Center the Back Plate over
the J Box and Secure the
back plate to the wall




Ensure watertight seal
using UL approved
silicone based sealant.

4




Connect Power
and Ground Wire.

5



6



7

Notice to installer :

- 1. WIRING INSTRUCTIONS** Warning : RISK OF FIRE AND ELECTRICAL SHOCK. : FIXTURE MUST BE INSTALLED BY A QUALIFIED ELECTRICIAN ONLY>FIXTURE IS INTENDED FOR INSTALLATION IN ACCORDANCE WITH THE NATIONAL ELECTRICAL CODE, LOCAL AND FEDERAL CODE SPECIFICATIONS. DISCONNECT POWER BEFORE SERVICING.
- 2. This fixture has a VOLTAGE SPECIFIC BALLAST, Check that the supply voltage is the same as the installed ballast voltage.**

Ligman Lighting USA

7144 NW Progress Court, Hillsboro
Oregon, 97124, USA
Tel : 503 645 0500 | Fax : 503 645 8100

www.ligmanlightingusa.com

UTA-31285/01/09/14/REV.2

1/1



FM-TS-13/25-05-2007-REV.2