

IP65: Suitable for Wet Locations

IK09: Impact Resistant (Vandal Resistant)

LUMINAIRE SPECIFICATION

Tel: 503-645-0500 Fax: 503-645-8100

7144 NW Progress Ct Hillsboro, Oregon 97124 www.ligmanlightingusa.com

USA-40149

Sandy 3 semi-recessed wall light LED

A range of small and large circular wall mounted bulkheads with polycarbonate diffuser. Ideal for numerous indoor or outdoor applications. Sandy has a subtle chamfered frame and it can be given a more striking appearance by way of different grill and visor options.

Low copper content corrosion resistant die-cast aluminum housing and frame. Stainless steel screws. Durable silicone rubber gasket and impact resistant UV stabilized polycarbonate diffuser. Housing is treated with a chemical chromatized protection before powder coating, ensuring high corrosion resistance. Integral electronic control gear. The sandy recessed wall light complies with ADA requirements.

Physical Data Diameter: 10.47" Weight: 3.9 lbs

Lamp

□ 20w - 400lm - White - LED ◎

LED Color (Please Specify)

□ W30 - 3000K □ W40 - 4000K

Voltage (Please Specify)

□ 120V

□ 277V

□ Other



Color (Please Specify)

□ 01-Black - RAL 9011

02- Dark Grey - RAL 7043

03-White - RAL 9003

04 - Metallic Silver - RAL 9006

□ 05-Matt Silver - RAL 9006 06-Bronze - RAL 6014

07- Custom - RAL






















Mounting detail





Ordering Example: USA - 40149 - White -20w - W30 - 120v - Options



DATE:



PROJECT:

QUANTITY:

NOTE: