



LUMINAIRE SPECIFICATION


Tel: 503-645-0500 7144 NW Progress Ct Fax: 503-645-8100 Hillsboro, Oregon 97124 www.ligmanlightingusa.com

IP65: Suitable for Wet Locations IK09: Impact Resistant (Vandal Resistant)









Mounting detail



Ordering Example: USA - 40170 - White-20w - W30 - 120v - Options

USA-40170

Sandy 5 semi-recessed wall light LED

A range of small and large circular wall mounted bulkheads with polycarbonate diffuser. Ideal for numerous indoor or outdoor applications. Sandy has a subtle chamfered frame and it can be given a more striking appearance by way of different grill and visor options.

Low copper content corrosion resistant die-cast aluminum housing and frame. Stainless steel screws. Durable silicone rubber gasket and impact resistant UV stabilized polycarbonate diffuser. Housing is treated with a chemical chromatized protection before powder coating, ensuring high corrosion resistance. Integral electronic control gear. The sandy recessed wall light complies with ADA requirements.

Physical Data Diameter: 10.47" Weight: 3.9 lbs

Lamp

□ 20w - 575lm - White - LED ⑩

LED Color (Please Specify)

- □ W30 3000K □ W40 4000K

Voltage (Please Specify)

- □ 120V
- □ 277V
- □ Other

Options (Please Specify)

Color (Please Specify)

- □ 01-Black RAL 9011
- □ 02- Dark Grey RAL 7043 □ 04 - Metallic Silver - RAL 9006
- □ 03-White RAL 9003 □ 05-Matt Silver - RAL 9006
- □ 07- Custom RAL
- 06-Bronze RAL 6014


















DATE:



PROJECT:

QUANTITY:

NOTE: