# **UVA-10073** Vancouver 37 Bollard







9.4"

**Top View** 

Ø5.9

**Mounting Detail** 

2.4'

9 4"


ŧ.

Ø.6"

Ø2.

## 21w COB 1571 Lumens

IK08 • Impact Resistant (Vandal Resistant) Weight 34.8 lbs



**IP65** • Suitable For Wet Locations

## Construction

Aluminum Less than 0.1% copper content – Marine Grade 6060 extruded & LM6 Aluminum High Pressure die casting provides excellent mechanical strength , clean detailed product lines and excellent heat dissipation.

### Pre paint

A step degrease and phosphate process that includes deoxidizing and etching as well as a zinc and nickel phosphate process before product painting.

### Memory Retentive -Silicon Gasket

Provided with special injection molded "fit for purpose" long life high temperature memory retentive silicon gaskets. Maintains the gaskets exact profile and seal over years of use and compression.

### Thermal management

I M6 Aluminum is used for its excellent mechanical strength and thermal dissipation properties in low and high ambient temperatures. The superior thermal heat sink design by Ligman used in conjunction with the driver, controls thermals below critical temperature range to ensure maximum luminous flux output, as well as providing long LED service life and ensuring less than 10% lumen depreciation at 50,000 hours.

# <u>Surge Suppression</u> Standard 10kv surge suppressor provided with all fixtures.

BUG Rating B1 - U1 - G0

### Finishing

All Ligman products go through an extensive finishing process that includes fettling to improve paint adherence.

### Paint

UV Stabilized 4.9Mil thick powder coat paint and baked at 200 C. This process ensures that Ligman products can withstand harsh environments. Rated for use in natatoriums.

Inspired by Nature Finishes The Inspired by nature Finishing is a unique system of decorative powder coating. Our metal decoration process can easily transform the appearance of metal or aluminum product into a wood grain finish

This patented technology enables the simulation of wood grain, and even marble or granite finish through the use of decorative powder coating.

The wood grain finish is so realistic that it's almost undistinguishable from real wood, even from a close visual inspection. The system of coating permeates the entire thickness of the coat and as a result, the coating cannot be removed by normal rubbing, chipping, or scratching.

The Coating Process After pre-treatment the prepared parts are powder coated with a specially formulated polyurethane powder. This powder provides protection against wear, abrasion, impact and corrosion and acts as the relief base color for the finalized metal decoration

The component is then wrapped with a sheet of non-porous film with the selected decoration pattern printed on it using special high temperature inks.

This printed film transfer is vacuum-sealed to the surface for a complete thermo print and then transferred into a customized oven. The oven transforms the ink into different forms within the paint layer before it becomes solid. Finally, the film is removed, and a vivid timber look on aluminum remains

Wood grain coating can create beautiful wood-looking products of any sort. There are over 300 combinations of designs currently in use. Wood grains can be made with different colors, designs, etc.

Our powder coatings are certified for indoor and outdoor applications and are backed by a comprehensive warranty. These coatings rise to the highest conceivable standard of performance excellence and design innovation.

### Added Benefits

 Resistance to salt-acid room, accelerated aging Boiling water, lime and condensed water resistant Anti-Graffiti, Anti-Slip, Anti-Microbial, Anti-Scratch Super durable (UV resistant) TGIC free (non-toxic)

### Hardware

Provided Hardware is Marine grade 316 Stainless steel.

### Anti Seize Screw Holes

Tapped holes are infused with a special anti seize compound designed to prevent seizure of threaded connections, due to electrolysis from heat, corrosive atmospheres and moisture.

### Crystal Clear Low Iron Glass Lens

LED still achieve 80% of their original flux)

Provided with tempered, impact resistant crystal clear low iron glass ensuring no green glass tinge.

### Optics & LED

Precise optic design provides exceptional light control and precise distribution of light. LED CRI > 80

<u>Lumen - Maintenance Life</u> L80 /B10 at 50,000 hours (This means that at least 90% of the

### Contemporary urban lighting furniture. Open-sided, three lattice pattern options or your bespoke design.

A stylish Dark Sky Compliant square high performance bollard with downward light distribution using LED lamps. This light column offers optimal visual comfort through glare control by utilizing a controlled optics designed by Ligman. These bollards have a square design providing a unique wide light distribution, offering an architecturally appealing clover leaf pattern on the paving. The internal sides of the supporting pillars are accented by light from the LED.

Color temperature 2700K, 3000K, 3500K and 4000K. The minimalistic shape provides distinctive lighting effects by night and decorative urban effect during the day. Suitable for pedestrian areas, precincts, building surrounds, shopping centers, squares and parks. The Vancouver Bollard comes standard with a unique waterproof internal driver housing compartment that is situated at the top of the pole to stop water and dust from entering the electrical components. This fixture is supplied completely wired with powercord and waterproof gland from the driver enclosure to the base of the column to ensure quick trouble-free installation.

The Vancouver has a specially designed anchor bolt mounting base that is partially buried below ground level to provide a flush fixture finish with the surface, but maintains the rigidity that is required when installing bollards.

Custom bollard heights are available, please specify. Provided with anchor bolts Reduced custom wattages can be provided to suit customer requirements. (Specify total watt requirement per fixture) Designed to complement the Vancouver Light Column UVA-20001

• NOTE: For the round version of the Vancouver, please see the Benton Light Column and Bollard






# UVA-10073

Vancouver 37 Bollard

LIGHTING USA





NAT - Natatorium Rated DIM - 0-10v Dimming HGT - Custom Bollard Height GFCI - GFCI Box

# More Custom Finishes Available Upon Request


Consult factory for pricing and lead times



Ligman Lighting USA reserves the right to change specifications without prior notice, please contact factory for latest information. Due to the continual improvements in LED technology data and components may change without notice



# Vancouver Product Family





Vancouver 11

• UVA-10021-21w-570Im [9.4"x9.4"-39.3']



• UVA-10031-21w-490Im [9.4"x9.4"-39.3']

Vancouver 12

Vancouver 13


• UVA-10041-21w-704lm [9.4"x9.4"-39.3']

Vancouver 14

• UVA-70001-8w-331lm [6.3"x6.3"-15.7"]



• UVA-70011-21w-815Im [9.4"x9.4"-15.7"]



Vancouver 19 • UVA-20141-33w-2858Im [9.4"x9.4"-13.3'] • UVA-20142-66w-4287Im [9.4"x9.4"-14.5'] • UVA-20143-99w-5716lm [9.4"x9.4"-15.7']


• UVA-20144-132w-7145Im [9.4"x9.4"-17']

Vancouver 17 Vancouver 18 • UVA-20121-33w-2858 lm [9.4"x9.4"-13.3'] • UVA-20131-33w-2858Im [9.4"x9.4"-13.3'] • UVA-20122-66w-4287Im [9.4"x9.4"-14.5'] • UVA-201312-66w-4287Im [9.4"x9.4"-14.5'] • UVA-20133-99w-5716Im [9.4"x9.4"-15.7"]

• UVA-20123-99w-5716Im [9.4"x9.4"-15.7"] • UVA-20124-132w-7145Im [9.4"x9.4"-17']

.

次第次第6次目20次目20次目20次目20次目20



• UVA-20112-66w-4287lm [9.4"x9.4"-14.5'] • UVA-20113-99w-5716lm [9.4"x9.4"-15.7"] • UVA-20114-132w-7145Im [9.4"x9.4"-17"]



• UVA-20134-132w-7145Im [9.4"x9.4"-17']



Vancouver 26

• UVA-30012-21w-490lm [6.3"x6.3"-23.6"]





Vancouver 28

• UVA-30021-39w-1336lm [9.4"x9.4"-39.3"] • UVA-30031-33w RGBW-429Im [9.4"x9.4"-39.3"]

Vancouver 29 • UVA-30022-39w-1167Im [9.4"x9.4"-39.3"]

• UVA-30032-33w RGBW-1158lm [9.4"x9.4"-39.3"]




Vancouver 20


• UVA-20151-33w-1429Im [9.4"x9.4"-12.1']

-----

## Vancouver 30

• UVA-30023-39w-1670Im [9.4"x9.4"-39.3"] • UVA-30033-33w RGBW-439Im [9.4"x9.4"-39.3"]







• UVA-70041-8w-165Im [6.3"x6.3"-15.7"]

• UVA-70051-21w-410Im [9.4"x9.4"-15.7"]

• UVA-30041-20w-1326Im [6.3."x6.3"-23.6"]

• UVA-30042-20w-1326Im [6.3."x6.3"-23.6"]

• UVA-30043-20w-1326Im [6.3."x6.3"-23.6"]







• UVA-30051-40w-2781lm [9.4"x9.4"-39.3"]

Vancouver 71 • UVA-30052-40w-2781lm [9.4"x9.4"-39.3"]



• UVA-30053-40w-2781lm [9.4"x9.4"-39.3"]