




40w COB 2781 Lumens IP65 • Suitable For Wet Locations IK08 • Impact Resistant Weight 34.8 lbs



Construction

Aluminum Less than 0.1% copper content – Marine Grade 6060 extruded & LM6 Aluminum High Pressure die casting provides excellent mechanical strength , clean detailed product lines and excellent heat dissipation.

Pre paint

8 step degrease and phosphate process that includes deoxidizing and etching as well as a zinc and nickel phosphate process before product painting.

Memory Retentive -Silicon Gasket

Provided with special injection molded "fit for purpose" long life high temperature memory retentive silicon gaskets.

Maintains the gaskets exact profile and seal over years of use and compression.

Thermal management

LM6 Aluminum is used for its excellent mechanical strength and thermal dissipation properties in low and high ambient temperatures. The superior thermal heat sink design by Ligman used in conjunction with the driver, controls thermals below critical temperature range to ensure maximum luminous flux output, as well as providing long LED service life and ensuring less than 10% lumen depreciation at 50,000

Surge Suppression
Standard 10kv surge suppressor provided with all fixtures.

BUG Rating Contact Factory

Finishing

All Ligman products go through an extensive finishing process that includes fettling to improve paint adherence

UV Stabilized 4.9Mil thick powder coat paint and baked at 200 Deg C. This process ensures that Ligman products can withstand harsh environments. Rated for use in natatoriums.

Inspired by Nature Finishes
The Inspired by nature Finishing is a unique system of decorative powder coating. Our metal decoration process can easily transform the appearance of metal or aluminum product into a wood grain finish.

This patented technology enables the simulation of wood grain, and even marble or granite finish through the use of decorative powder coating.

The wood grain finish is so realistic that it's almost undistinguishable from real wood, even from a close visual inspection. The system of coating permeates the entire thickness of the coat and as a result, the coating cannot be removed by normal rubbing, chipping, or scratching

After pre-treatment the prepared parts are powder coated with a specially formulated polyurethane powder. This powder provides protection against wear, abrasion, impact and corrosion and acts as the relief base color for the finalized metal

The component is then wrapped with a sheet of non-porous film with the selected decoration pattern printed on it using special high temperature inks.

This printed film transfer is vacuum-sealed to the surface for a complete thermo print and then transferred into a customized oven. The oven transforms the ink into different forms within the paint layer before it becomes solid. Finally, the film is removed, and a vivid timber look on aluminum remains

Wood grain coating can create beautiful wood-looking products of any sort. There are over 300 combinations of designs currently in use. Wood grains can be made with different colors, designs, etc.

Our powder coatings are certified for indoor and outdoor applications and are backed by a comprehensive warranty. These coatings rise to the highest conceivable standard of performance excellence and design innovation.

- Resistance to salt-acid room, accelerated aging
 Boiling water, lime and condensed water resistant
 Anti-Graffiti, Anti-Slip, Anti-Microbial, Anti-Scratch
- Super durable (UV resistant)

<u>Hardware</u> Provided Hardware is Marine grade 316 Stainless steel.

Anti Seize Screw Holes
Tapped holes are infused with a special anti seize compound designed to prevent seizure of threaded connections, due to electrolysis from heat, corrosive atmospheres and moisture.

Crystal Clear Low Iron Glass Lens

Provided with tempered, impact resistant crystal clear low iron glass ensuring no green glass tinge. Optics & LED Precise optic design provides exceptional light control and

precise distribution of light.

<u>Lumen - Maintenance Life</u> L80 /B10 at 50,000 hours (This means that at least 90% of the LED still achieve 80% of their original flux)

Contemporary urban lighting furniture. Open-sided, three lattice pattern options or your bespoke design.

A stylish Dark Sky Compliant square high performance wall mounted luminaire with downward light distribution using LED lamps. This light column offers optimal visual comfort through glare control by utilizing a controlled optics designed by Ligman. These luminaires have a square design providing a unique wide light distribution, offering an architecturally appealing shadow pattern on the mounted surface. The internal sides of the supporting pillars are accented by light from the LED.

Color temperature 2700K, 3000K, 3500K and 4000K and RGBW. The minimalistic shape provides distinctive lighting effects by night and decorative urban effect during the day. Suitable for pedestrian areas, precincts, building surrounds, shopping centers, squares and parks. The Vancouver comes standard with a unique waterproof internal driver housing compartment that is situated at the top of the pole to stop water and dust from entering the electrical components. This fixture is supplied completely wired with powercord and waterproof gland from the driver enclosure to the base of the column to ensure quick trouble-free installation.

Custom heights are available, please specify in options. Designed to complement the Vancouver Light Column and bollard.



UVA-30051

Vancouver 70 Surface



PROJECT DATE NOTE **QUANTITY TYPE** ORDERING EXAMPLE || UVA - 30051- 40w - W30 - 02 - 120/277v - Options UVA-30051 **LAMP** LED COLOR **FINISH COLOR VOLTAGE** 40w COB W27 - 2700K 01 - BLACK RAL 9011 120/277v Other - Specify 2781 Lumens W30 - 3000K 02 - DARK GREY RAL 7043 W35 - 3500K 03 - WHITE RAL 9003 W40 - 4000K 04 - METALLIC SILVER RAL 9006 05 - MATTE SILVER RAL 9006 06 - LIGMAN BRONZE 07 - CUSTOM RAL **INSPIRED BY NATURE FINISHES** SW01 - OAK FINISH SW02 - WALNUT FINISH SW03- PINE FINISH **ADDITIONAL OPTIONS** DF - DOUGLAS FIR FINISH THERE IS AN ADDITIONAL CW - CHERRY WOOD FINISH NAT - Natatorium Rated COST FOR THESE FINISHES NW - NATIONAL WALNUT FINISH F - Frosted Lens SU01 - CONCRETE FINISH OB - Open Bottom SU02 - SOFTSCAPE FINISH

> SU03 - STONE FINISH SU04 - CORTEN FINISH

More Custom Finishes Available Upon Request

Consult factory for pricing and lead times


HGT - Custom Height [Specify]







Vancouver Product Family




• UVA-20001-40w-2969Im [9.4"x9.4"-14.7"]



• UVA-10001-21w-1270Im [9.4"x9.4"-39.3"]



• UVA-10011-15w-837lm [6.3"x6.3"-39.3"]




• UVA-20021-39/21w-1336/1673lm [9.4"x9.4"-13.3']

- UVA-20022-39/2x21w-1336/2x1673lm [9.4"x9.4"-14.5"]
- UVA-20023-39/3x21w-1336/3x1673Im [9.4"x9.4"-15.7']



• UVA-20031-39/21w-1167/1673lm [9.4"x9.4"-13.3']

- UVA-20032-39/2x21w-1167/2x1673lm [9.4"x9.4"-14.5"]
- UVA-20033-39/3x21w-1167/3x1673lm [9.4"x9.4"-15.7']




• UVA-20041-39/21w-1670/1673lm [9.4"x9.4"-13.3']


- UVA-20042-39/2x21w-1670/2x1673Im [9.4"x9.4"-14.5"]
- UVA-20043-39/3x21w-1670/3x1673lm [9.4"x9.4"-15.7']



• UVA-20051-40w-1336lm [9.4"x9.4"-12.1']



• UVA-20061-40w-1167lm [9.4"x9.4"-12.1']



• UVA-20071-40w-1670lm [9.4"x9.4"-12.1']



• UVA-10021-21w-570lm [9.4"x9.4"-39.3']



• UVA-10031-21w-490Im [9.4"x9.4"-39.3']



Vancouver 13 • UVA-10041-21w-704lm [9.4"x9.4"-39.3']



Vancouver 14 • UVA-70001-8w-331lm [6.3"x6.3"-15.7"]



• UVA-70011-21w-815lm [9.4"x9.4"-15.7"]



Vancouver 16

- UVA-20111-33w-1429Im [9.4"x9.4"-13.3']
- UVA-20112-66w-4287lm [9.4"x9.4"-14.5'] • UVA-20113-99w-5716lm [9.4"x9.4"-15.7"]
- UVA-20114-132w-7145lm [9.4"x9.4"-17"]



Vancouver 17

- UVA-20121-33w-2858 lm [9.4"x9.4"-13.3']
- UVA-20122-66w-4287lm [9.4"x9.4"-14.5'] • UVA-20123-99w-5716Im [9.4"x9.4"-15.7"]
- UVA-20124-132w-7145lm [9.4"x9.4"-17"]




Vancouver 18

- UVA-20131-33w-2858Im [9.4"x9.4"-13.3']
- UVA-201312-66w-4287lm [9.4"x9.4"-14.5'] • UVA-20133-99w-5716Im [9.4"x9.4"-15.7"]
- UVA-20134-132w-7145lm [9.4"x9.4"-17"]



Vancouver 19


- UVA-20141-33w-2858lm [9.4"x9.4"-13.3']
- UVA-20142-66w-4287lm [9.4"x9.4"-14.5']
- UVA-20143-99w-5716Im [9.4"x9.4"-15.7'] • UVA-20144-132w-7145lm [9.4"x9.4"-17']



• UVA-20151-33w-1429Im [9.4"x9.4"-12.1"]

Vancouver 21

• UVA-20161-33w-1429lm [9.4"x9.4"-12.1']



Vancouver 22

• UVA-20171-33w-1429Im [9.4"x9.4"-12.1']



Vancouver 23

• UVA-20181-33w-1429lm [9.4"x9.4"-12.1']



Vancouver 24

• UVA-30001-8w-331lm [6.3"x6.3"-15.7"]



Vancouver 25

• UVA-30011-21w-570Im [6.3"x6.3"-23.6"]



Vancouver 26

• UVA-30012-21w-490lm [6.3"x6.3"-23.6"]



Vancouver 27

• UVA-30013-21w-740Im [6.3"x6.3"-23.6"]



Vancouver 28

• UVA-30021-39w-1336lm [9.4"x9.4"-39.3"] • UVA-30031-33w RGBW-429lm [9.4"x9.4"-39.3"]




Vancouver 29

• UVA-30022-39w-1167lm [9.4"x9.4"-39.3"] • UVA-30032-33w RGBW-1158lm [9.4"x9.4"-39.3"]



Vancouver 30

• UVA-30023-39w-1670Im [9.4"x9.4"-39.3"] • UVA-30033-33w RGBW-439Im [9.4"x9.4"-39.3"]



Vancouver 42

Vancouver 43

Vancouver 44

Vancouver 45

Vancouver 45

Vancouver 46


· UVA-20201-40w-2969 Im [9.4" x 9.4" - 14.7]

· UVA-20211-39/21w-2781/1688Im [9.4"x9.4"-13.3]

· UVA-20212-39/2x21w-2781/2x1688Im [9.4"x9.4"-14.5]

· UVA-20213-39/3x21w-2781/3x1688Im [9.4"x9.4"-15.7]

· UVA-20221-39/21w-4469/1688Im [9.4"x9.4"-13.3]



• UVA-20281-76w-4140lm [9.4°x9.4°-12] • UVA-20282-76w-4140lm [9.4°x9.4°-12] • UVA-20283-76w-4140lm [9.4°x9.4°-12] • UVA-70021-13w-437lm [6.3°x6.3°-15.7°] • UVA-70031-20w-1362lm [9.4°x9.4°-15.7°]



• UVA-70041-8w-165Im [6.3"x6.3"-15.7"]



• UVA-70051-21w-410lm [9.4"x9.4"-15.7"]



Vancouver 67

• UVA-30041-20w-1326Im [6.3."x6.3"-23.6"]



Vancouver 68

• UVA-30042-20w-1326lm [6.3.*x6.3*-23.6*]



Vancouver 69

• UVA-30043-20w-1326Im [6.3."x6.3"-23.6"]



Vancouver 70

• UVA-30051-40w-2781lm [9.4"x9.4"-39.3"]



Vancouver 71

• UVA-30052-40w-2781lm [9.4"x9.4"-39.3"]



Vancouver 72

• UVA-30053-40w-2781lm [9.4"x9.4"-39.3"]