






# INSTALLATION AND SERVICE MANUAL



**LIGMAN**  
LIGHTING USA

For Installation of Frame bollard.

Product drawing (dimensions) SUITABLE FOR WET LOCATIONS



Connect power  
and Ground wire



**Ligman RGBW/DMX & 0-10v dimming fixtures are provided with 5 wire, underwater rated 600v SO power cord. This consists of hot, neutral and ground, as well as twisted, shielded DMX +, DMX - and ground wire.**

## Notice to installer :

- 1.WIRING INSTRUCTIONS** Warning : RISK OF FIRE AND ELECTRICAL SHOCK. : FIXTURE MUST BE INSTALLED BY A QUALIFIED ELECTRICIAN ONLY>FIXTURE IS INTENDED FOR INSTALLATION IN ACCORDANCE WITH THE NATIONAL ELECTRICAL CODE, LOCAL AND FEDERAL CODE SPECIFICATIONS. DISCONNECT POWER BEFORE SERVICING.
- 2.This fixture has a VOLTAGE SPECIFIC BALLAST,**Check that the supply voltage is the same as the installed ballast voltage.


**Ligman Lighting USA**

# DMX WIRING DIAGRAM



GREEN	GROUND
BLACK	120/277 HOT
WHITE	NEUTRAL
YELLOW	DMX GROUND
PURPLE	DMX +
GREY	DMX -

## SINGLE FIXTURE CONNECTION



## FOR LOOPING TO MULTIPLE FIXTURES

